



Specifications

Frequency Range: 29-512 MHz
 Dimensions: 14" x 17.5" x 5.5"
 Weight: 17 Ounces
 Audio Output: 2 Watts
 Sensitivity: LB .3 uv/m, HB .4 uv/m, UHF .5 uv/m @ 12 dB SINAD
 Frequency Control: Single channel synthesized
 Programming: Internal by dealer
 Standard decode Format: Two Tone Sequential
 Optional formats: CTCSS, DTMF
 Code Capacity - 2 Individual calls plus Group call
 Operating voltage: 13.8 VDC (\pm 10%)
 Antenna Jack: BNC Type
 Remote Switch Jack (Optional) 3.5 mm IMP
 Output impedance: 4 Ohms
 Operating temperature: -20C to 60C
 Factory Warranty: One year



Our 2TR9.....

fixed alert monitor receiver provides essentially the same functions as a personal alert voice monitor receiver such as the Motorola Minitor V or US Alert WatchDog. The 2TR9 can be selectively called using standard 2-tone codes to alert personnel in a fixed location such as a fire station, school, or other locations that need to be alerted in times of emergency. If desired, the 2TR9 can be used for connection to an external PA system. The applications are as limitless as your imagination! Additional information is available by reviewing the *Specifications* section on the left. You can order on line by going to www.bestpriceradio.com, click on *Search*, and enter *Veetronix*.

Prices

Basic 2TR9 with DC Wall transformer, telescoping antenna and programming on the frequency and 2-tone codes of your choice.	\$310.00
2TPGK - Programming kit	50.00
2TRSO - Relay kit for control of external devices (sirens, doors, etc.)	35.00
2TBUP - Battery backup	50.00
2TCTC - CTCSS decode	50.00
2TDTM - DTMF decode	50.00

Normal delivery - 30 days or less

The 2TR9 is just one of a family of selective call receiver products available from Falcon Direct. See www.info4u.us/PagerModels.pdf for information on other alerting communications products.

36 – 20th Avenue NW - Birmingham, AL 35215 - Phone 205.854.2611 - Fax 205.853.6178
 Visit our Blog at <http://falconinfo.blogspot.com> or our web site at www.falcondirect.com